

SAFETY DATA SHEET

Based on Directive 2001/58/EC of the Commission of the European Communities

SPS ACTIVATOR

1. Identification of the substance/preparation and the company

1.1 Identification of the substance or preparation:

- Not applicable

1.2 Use of the substance or the preparation:

Cleaner

1.3 Company/undertaking identification:

SODAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
Tel. : +32 14 42 42 31
Fax : +32 14 44 39 71

1.4 Telephone number for emergency:

+32 14 58 45 45
Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.)
Technische Schoolstraat 43 A, B-2440 Geel

2. Composition/information on ingredients

Hazardous ingredients	CAS No. EINECS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
propan-2-ol	67-63-0 200-661-7	> 25	F;Xn	11-36-65-67 (1)
titanium tetraisopropanolate	546-68-9 208-909-6	< 20	Xi	10-36/37/38 (1)

(1) For R-phrases in full: see heading 16

3. Hazards identification

- Highly flammable
- Irritant to the eyes
- Vapours may cause drowsiness and dizziness

4. First aid measures

4.1 Eye contact:

- Rinse immediately with plenty of water
- Seek medical advice

4.2 Skin contact:

- Wash immediately with lots of water
- If irritation persists: seek medical advice

4.3 After inhalation:

- Remove the victim into fresh air
- Seek medical advice

4.4 After ingestion:

- Never give water to an unconscious person
- Do not induce vomiting
- Seek medical advice

Printing date : 11-2005
Compiled by : Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
☎ +32 14 58 45 47 <http://www.big.be> E-mail: info@big.be

MSDS established : 11-05-2002 Revision date : 17-12-2003
Reference number : BIG\32156GB Revision number : 004
Reason for revision : See heading 14.5

1/9

SPS ACTIVATOR

5. Fire-fighting measures

5.1 Suitable extinguishing media:

- Water spray
- Polyvalent foam
- Alcohol-resistant foam
- BC powder
- Carbon dioxide

5.2 Unsuitable extinguishing media:

- Solid water jet ineffective as extinguishing medium

5.3 Special exposure hazards:

- On burning: release of carbon monoxide and carbon dioxide
- Gas/vapour spreads at floor level: ignition hazard

5.4 Instructions:

- Cool drums with water spray
- Do not move the load if exposed to heat

5.5 Special protective equipment for firefighters:

- Heat/fire exposure: compressed air/oxygen apparatus

6. Accidental release measures

6.1 Personal protection/precautions: see heading 8.1/8.3/10.3

6.2 Environmental precautions:

- Use appropriate containment to avoid environmental contamination

6.3 Clean-up:

- Take up liquid spill into absorbent material e.g.: dry sand/earth
- Take collected spill to competent authority
- Wash clothing and equipment after handling

7. Handling and storage

7.1 Handling:

- Observe strict hygiene
- In case of insufficient ventilation: keep naked flames/sparks away
- Do not discharge the waste into the drain

7.2 Storage:

- Keep container tightly closed
- Store in a cool area
- Store in a dry area

- Keep away from: heat sources, ignition sources, oxidizing agents, acids, bases, halogens

Storage temperature	:	Roomtemperature
Quantity limits	:	N.D. kg
Storage life	:	365 days
Materials for packaging	:	
- suitable	:	tin

7.3 Specific uses:

- See information supplied by the manufacturer

SPS ACTIVATOR

8. Exposure controls/Personal protection

8.1 Exposure limit values:

PROPAN-2-OL:

TLV-TWA	: -	mg/m ³	(400)	ppm
TLV-STEL	: -	mg/m ³	(500)	ppm
TLV-Ceiling	: -	mg/m ³	-	ppm
OES-LTEL	: 999	mg/m ³	400	ppm
OES-STEL	: 1250	mg/m ³	500	ppm
MAK	: 500	mg/m ³	200	ppm
TRK	: -	mg/m ³	-	ppm
MAC-TGG 8 h	: 650	mg/m ³		
MAC-TGG 15 min.	: -	mg/m ³		
MAC-Ceiling	: -	mg/m ³		
VME-8 h	: -	mg/m ³	-	ppm
VLE-15 min.	: 980	mg/m ³	400	ppm
GWBB-8 h	: 997	mg/m ³	400	ppm
GWK-15 min.	: 1248	mg/m ³	500	ppm
Momentary value	: -	mg/m ³	-	ppm
EC	: -	mg/m ³	-	ppm
EC-STEL	: -	mg/m ³	-	ppm

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Use only in well ventilated area

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- In case of insufficient ventilation: respiratory protection with filtertype A

8.3.2 hand protection:

- Gloves
suitable materials:

GIVE GOOD RESISTANCE:
Butyl rubber
Nitrile rubber
Viton
Neoprene
Chloroprene rubber
Chlorosulfonated polyethylene
Tetrafluoroethylene

8.3.3 eye protection:

- Safety glasses

8.3.4 skin protection:

- Heatproof clothing
suitable materials:

GIVE GOOD RESISTANCE:
Butyl rubber
Nitrile rubber
Viton
Neoprene
Chloroprene rubber
Chlorosulfonated polyethylene
Tetrafluoroethylene

SPS ACTIVATOR

9. Physical and chemical properties

9.1 General information:

Appearance (at 20°C)	: Liquid
Odour	: Alcohol
Colour	: Colourless

9.2 Important health, safety and environmental information:

pH value	: N.D.	
Boiling point/boiling range	: > 82	°C
Flashpoint	: 12	°C
Explosion limits	: 2 - 12	Vol%
Vapour pressure (at 20°C)	: 43	hPa
Vapour pressure (at 50°C)	: 295	hPa
Relative density (at 20°C)	: 0.8	
Water solubility	: Soluble	
Soluble in	: Ether, chloroform	
Relative vapour density	: 2.1	
Viscosity (at 20°C)	: N.D.	Pa.s
Partition coefficient n-octanol/water	: N.D.	
Evaporation rate		
ratio to butyl acetate	: N.D.	
ratio to ether	: N.D.	

9.3 Other information:

Melting point/melting range	: N.D.	°C
Auto-ignition point	: N.D.	°C
Saturation concentration	: N.D.	g/m ³

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- Keep away from: heat sources, ignition sources, oxidizing agents, acids, bases, halogens

10.3 Hazardous decomposition products:

- On burning: release of carbon monoxide and carbon dioxide
- Violent to explosive reaction with (strong) oxidizers
- Reacts exothermically with (some) metals
- Prolonged storage/in large quantities: may form peroxides

11. Toxicological information

11.1 Acute toxicity:

PROPAN-2-OL:

LD50 oral rat	: 4710	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: 12870	mg/kg
LC50 inhalation rat	: > 20	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

TITANIUM TETRAISOPROPANOLATE:

LD50 oral rat	: 7460	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

11.2 Chronic toxicity:

PROPAN-2-OL:

EC carc. cat. : not listed
EC muta. cat. : not listed
EC repr. cat. : not listed

Carcinogenicity (TLV) : (A4)
Carcinogenicity (MAC) : not listed
Carcinogenicity (VME) : not listed
Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : not listed
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : group C

IARC classification : 3

11.3 Routes of exposure: ingestion, inhalation, eye and skin

11.4 Acute effects/symptoms:

AFTER INHALATION:

EXPOSURE TO HIGH CONCENTRATIONS:

- Irritation of the respiratory tract
- Dry/sore throat
- CNS depression
- Dizziness
- Headache
- Narcosis

AFTER INGESTION:

AFTER ABSORPTION OF HIGH QUANTITIES:

- CNS depression
- Disturbed motor response
- Headache
- Disturbances of consciousness
- Dilatation of the blood vessels
- Low arterial pressure
- Vomiting
- Nausea
- Abdominal pain
- Risk of aspiration pneumonia

FOLLOWING SYMPTOMS MAY APPEAR LATER:

- Body temperature fall
- Slowing respiration

AFTER EYE CONTACT:

- Irritation of the eye tissue

11.5 Chronic effects:

- Contains substance with uncertain teratogenic properties (propan-2-ol)

ON CONTINUOUS EXPOSURE/CONTACT:

- Red skin
- Dry skin
- Itching
- Skin rash/inflammation
- Impaired memory
- Cracking of the skin

SPS ACTIVATOR

12. Ecological information

12.1 Ecotoxicity:

PROPAN-2-OL:

- LC50 (96 h) : 9640 mg/l (PIMEPHALES PROMELAS)
- EC50 (48 h) : 13299 mg/l (DAPHNIA MAGNA)
- EC50 (72 h) : >1000 mg/l (SCENEDESMUS SUBSPICATUS)

12.2 Mobility:

- Volatile organic compounds (VOC): 100 %
- Insoluble in water

For other physicochemical properties see section 9

12.3 Persistence and degradability:

- biodegradation BOD₅ : N.D. % ThOD
- water : No data available
- soil : T ½ N.D. days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D.
- BCF : N.D.

12.5 Other adverse effects:

- WGK : 1 (classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : No data available
- Effect on waste water purification : No data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 14 06 03 (other solvents and solvent mixtures)
- Waste material code (Flanders): 015
- Hazardous waste (91/689/EEC)

13.2 Disposal methods:

- Do not discharge into surface water

13.3 Packaging:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10 (packaging containing residues of or contaminated by dangerous substances)

14. Transport information

33

1993

14.1 Classification of the substance in compliance with UN Recommendations

```

UN number           : 1993
CLASS               : 3
SUB RISKS           : -
PACKING             : II
PROPER SHIPPING NAME :
UN 1993, Flammable liquid, n.o.s. having a vapour pressure at 50 °C of not more
than 110 kPa (1,10 bar)
(propan-2-ol)
    
```

14.2 ADR (transport by road)

```

CLASS               : 3
PACKING             : II
DANGER LABEL TANKS : 3
DANGER LABEL PACKAGES : 3
    
```

14.3 RID (transport by rail)

```

CLASS               : 3
PACKING             : II
DANGER LABEL TANKS : 3
DANGER LABEL PACKAGES : 3
    
```

14.4 ADNR (transport by inland waterways)

```

CLASS               : 3
PACKING             : II
DANGER LABEL TANKS : 3
DANGER LABEL PACKAGES : 3
    
```

14.5 IMDG (maritime transport)

```

CLASS               : 3
SUB RISKS           : -
PACKING             : II
MFAG                : -
EMS                 : F-E, S-E
MARINE POLLUTANT    : -
    
```

14.6 ICAO (air transport)

```

CLASS               : 3
SUB RISKS           : -
PACKING             : II
PACKING INSTRUCTIONS PASSENGER AIRCRAFT : 305/Y305
PACKING INSTRUCTIONS CARGO AIRCRAFT    : 307
    
```

14.7 Special precautions in connection with transport : None

14.8 Limited quantities (LQ) :

When substances and their packaging meet the conditions established by ADR/RID/ADNR in chapter 3.4, **only** the following prescriptions shall be complied with:

each package shall display a diamond-shaped figure with the following inscription:

- 'UN 1993'

or, in the case of different goods with different identification numbers within a single package:

- the letters 'LQ'

SPS ACTIVATOR

15. Regulatory information

Labelling in accordance with EC directives 67/548/EEC and 1999/45/EC
(** : see heading 16)



Highly flammable



Irritant

- R36 : Irritant to the eyes
R67 : Vapours may cause drowsiness and dizziness
- S(02) : (Keep out of reach of children)
S07 : Keep container tightly closed
S16 : Keep away from sources of ignition - No smoking
S24/25 : Avoid contact with skin and eyes
S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

16. Other information

De informatie in dit veiligheidsblad werd opgesteld naar best vermogen, en geeft de stand van kennis weer op het ogenblik van publicatie. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
***** = INTERNAL CLASSIFICATION

(**) Labelling:

The labelling of the substance described in this MSDS complies with the provisions of Directive 1999/45/EC of 31 May 1999, published in the Official Journal of the European Communities L 200 of 30/07/1999. This Directive replaces Directive 88/379/EEC of 7 June 1988, published in the Official Journal of the European Communities L 187 of 16/07/1988.

Member States shall apply the laws, regulations and administrative provisions referred to in article 22 of this Directive:

- (a) to preparations not within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2002; and
(b) to preparations within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2004.

Full text of any R-phrases referred to under heading 2:

R10 : Flammable
R11 : Highly flammable
R36 : Irritant to the eyes
R36/37/38 : Irritating to eyes, respiratory system and skin
R65 : Harmful: may cause lung damage if swallowed
R67 : Vapours may cause drowsiness and dizziness

Exposure limits:

TLV : Threshold Limit Value - ACGIH USA 2002
OES : Occupational Exposure Standards - United Kingdom 2001
MEL : Maximum Exposure Limits - United Kingdom 2001
MAK : Maximale Arbeitsplatzkonzentrationen - Germany 2001
TRK : Technische Richtkonzentrationen - Germany 2001
MAC : Maximale aanvaarde concentratie - The Netherlands 2002
VME : Valeurs limites de Moyenne d'Exposition - France 1999
VLE : Valeurs Limites d'Exposition à court terme - France 1999
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium 2002
GWK : Grenswaarde kortstondige blootstelling - Belgium 2002
EC : Indicative occupational exposure limit values - Directive 2000/39/EC

I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil
R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a:	aerosol	r:	rook/Rauch	(fume)
d:	damp (vapour)	st:	stof/Staub	(dust)
du:	dust	ve:	vezel	(fibre)
fa:	Faser (fibre)	va:	vapour	
fi:	fibre	om:	oil mist	
fu:	fume	on:	olienevel/Ölnebel	(oil mist)
p:	poussière (dust)	part:	particles	

Chronic toxicity:

K: List of the carcinogenic substances and processes - The Netherlands 2000