

# SAFETY DATA SHEET

Based on Directive 2001/58/EC of the Commission of the European Communities

## Profil Adapterfoam

### 1. Identification of the substance/preparation and of the company/undertaking

#### 1.1 Identification of the substance or preparation:

- Not applicable

#### 1.2 Use of the substance or the preparation:

- Isolation

#### 1.3 Company/undertaking identification:

SODAL N.V.  
Everdongenlaan 18-20  
B-2300 Turnhout  
Tel. : +32 14 42 42 31  
Fax : +32 14 44 39 71

#### 1.4 Telephone number for emergency:

+32 14 58 45 45  
Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.)  
Technische Schoolstraat 43 A, B-2440 Geel

### 2. Composition/information on ingredients

Hazardous ingredients	CAS No. EINECS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
polymethylenepolyphenylisocyanate	9016-87-9 -	> 25	Xn	20-36/37/38-42/43 (1)
alpha,alpha',alpha''-1,2,3- propanetriyltris(omega-hydroxy-) poly[oxy(methyl-1,2-ethanediyl)]	25791-96-2 500-044-5	< 25	Xn	22 (1)
isobutane	75-28-5 200-857-2	1 - 10	F+	12 (1)
dimethyl ether	115-10-6 204-065-8	1 - 5	F+	12 (1)
propane	74-98-6 200-827-9	1 - 5	F+	12 (1)

(1) For R-phrases in full: see heading 16

### 3. Hazards identification

- Extremely flammable
- Harmful by inhalation
- Irritating to eyes, respiratory system and skin
- May cause sensitization by inhalation and skin contact

Printing date : 09-2004 1/11  
Compiled by : Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)  
Technische Schoolstraat 43 A, B-2440 Geel  
☎ +32 14 58 45 47 http://www.big.be E-mail: info@big.be

MSDS established : 05-04-2002 Revision date : 18-12-2003  
Reference number : BIG\32973GB Revision number : 005  
Reason for revision : See heading 14.5

# Profil Adapterfoam

## 4. First aid measures

- 4.1 Eye contact:**
- Rinse immediately with plenty of water
  - Seek medical advice
- 4.2 Skin contact:**
- Wash immediately with lots of water
  - If irritation persists: seek medical advice
- 4.3 After inhalation:**
- Remove the victim into fresh air
  - Seek medical advice
- 4.4 After ingestion:**
- Never give water to an unconscious person
  - Seek medical advice

## 5. Fire-fighting measures

- 5.1 Suitable extinguishing media:**
- Quantities of water
  - Polyvalent foam
  - BC powder
  - Carbon dioxide
- 5.2 Unsuitable extinguishing media:**
- None
- 5.3 Special exposure hazards:**
- On heating: release of toxic/combustible gases/vapours: nitrous vapours, hydrogen chloride, carbon monoxide and carbon dioxide
  - Gas/vapour spreads at floor level: ignition hazard
  - Vapour-air mixture is flammable/explosive within the explosion limits
  - Aerosol may explode under the effect of heat
- 5.4 Instructions:**
- Dilute toxic gases with water spray
  - Do not move the load if exposed to heat
- 5.5 Special protective equipment for firefighters:**
- Heat/fire exposure: compressed air/oxygen apparatus

## 6. Accidental release measures

- 6.1 Personal protection/precautions:**
- See heading 8.1/8.3/10.3
- 6.2 Environmental precautions:**
- Use appropriate containment to avoid environmental contamination
- 6.3 Methods of cleaning up:**
- Allow product to solidify and remove it by mechanical means
  - Remove uncured foam with acetone

# Profil Adapterfoam

## 7. Handling and storage

### 7.1 Handling:

- Observe very strict hygiene - avoid contact
- In case of insufficient ventilation: keep naked flames/sparks away
- Remove contaminated clothing immediately/reinigen

### 7.2 Storage:

- Keep out of direct sunlight
- Keep away from: heat sources, ignition sources, acids, bases

Storage temperature	: < 50	°C
Quantity limit	: N.D.	kg
Storage life	: 365	days
Materials for packaging	:	
- suitable	: aerosol dispenser	

### 7.3 Specific uses:

- See information supplied by the manufacturer

## 8. Exposure controls/Personal protection

### 8.1 Exposure limit values:

POLYMETHYLENENOLYPHENYLISOCYANATE:

TLV-TWA	: -	mg/m <sup>3</sup>	-	ppm
TLV-STEL	: -	mg/m <sup>3</sup>	-	ppm
TLV-Ceiling	: -	mg/m <sup>3</sup>	-	ppm
MEL-LTEL	: 0.02 (-NCO)	mg/m <sup>3</sup>	-	ppm
MEL-STEL	: 0.07 (-NCO)	mg/m <sup>3</sup>	-	ppm
MAK	: -	mg/m <sup>3</sup>	-	ppm
TRK	: -	mg/m <sup>3</sup>	-	ppm
MAC-TGG 8 h	: -	mg/m <sup>3</sup>	-	
MAC-TGG 15 min.	: -	mg/m <sup>3</sup>	-	
MAC-Ceiling	: -	mg/m <sup>3</sup>	-	
VME-8 h	: -	mg/m <sup>3</sup>	-	ppm
VLE-15 min.	: -	mg/m <sup>3</sup>	-	ppm
GWBB-8 h	: -	mg/m <sup>3</sup>	-	ppm
GWK-15 min.	: -	mg/m <sup>3</sup>	-	ppm
Momentary value	: -	mg/m <sup>3</sup>	-	ppm
EC	: -	mg/m <sup>3</sup>	-	ppm
EC-STEL	: -	mg/m <sup>3</sup>	-	ppm

## Profil Adapterfoam

### ISOBUTANE :

TLV-TWA	: -	mg/m <sup>3</sup>	-	ppm
TLV-STEL	: -	mg/m <sup>3</sup>	-	ppm
TLV-Ceiling	: -	mg/m <sup>3</sup>	-	ppm
OES-LTEL	: -	mg/m <sup>3</sup>	-	ppm
OES-STEL	: -	mg/m <sup>3</sup>	-	ppm
MAK	: 2400	mg/m <sup>3</sup>	1000	ppm
TRK	: -	mg/m <sup>3</sup>	-	ppm
MAC-TGG 8 h	: -	mg/m <sup>3</sup>		
MAC-TGG 15 min.	: -	mg/m <sup>3</sup>		
MAC-Ceiling	: -	mg/m <sup>3</sup>		
VME-8 h	: -	mg/m <sup>3</sup>	-	ppm
VLE-15 min.	: -	mg/m <sup>3</sup>	-	ppm
GWBB-8 h	: -	mg/m <sup>3</sup>	-	ppm
GWK-15 min.	: -	mg/m <sup>3</sup>	-	ppm
Momentary value	: -	mg/m <sup>3</sup>	-	ppm
EC	: -	mg/m <sup>3</sup>	-	ppm
EC-STEL	: -	mg/m <sup>3</sup>	-	ppm

### DIMETHYL ETHER :

TLV-TWA	: -	mg/m <sup>3</sup>	-	ppm
TLV-STEL	: -	mg/m <sup>3</sup>	-	ppm
TLV-Ceiling	: -	mg/m <sup>3</sup>	-	ppm
OES-LTEL	: -	mg/m <sup>3</sup>	400	ppm
OES-STEL	: -	mg/m <sup>3</sup>	500	ppm
MAK	: 1900	mg/m <sup>3</sup>	1000	ppm
TRK	: -	mg/m <sup>3</sup>	-	ppm
MAC-TGG 8 h	: 950	mg/m <sup>3</sup>		
MAC-TGG 15 min.	: 1500	mg/m <sup>3</sup>		
MAC-Ceiling	: -	mg/m <sup>3</sup>		
VME-8 h	: -	mg/m <sup>3</sup>	-	ppm
VLE-15 min.	: -	mg/m <sup>3</sup>	-	ppm
GWBB-8 h	: -	mg/m <sup>3</sup>	-	ppm
GWK-15 min.	: -	mg/m <sup>3</sup>	-	ppm
Momentary value	: -	mg/m <sup>3</sup>	-	ppm
EC	: 1920	mg/m <sup>3</sup>	1000	ppm
EC-STEL	: -	mg/m <sup>3</sup>	-	ppm

### PROPANE :

TLV-TWA	: -	mg/m <sup>3</sup>	2500	ppm
TLV-STEL	: -	mg/m <sup>3</sup>	-	ppm
TLV-Ceiling	: -	mg/m <sup>3</sup>	-	ppm
OES-LTEL	: -	mg/m <sup>3</sup>	-	ppm
OES-STEL	: -	mg/m <sup>3</sup>	-	ppm
MAK	: 1800	mg/m <sup>3</sup>	1000	ppm
TRK	: -	mg/m <sup>3</sup>	-	ppm
MAC-TGG 8 h	: -	mg/m <sup>3</sup>		
MAC-TGG 15 min.	: -	mg/m <sup>3</sup>		
MAC-Ceiling	: -	mg/m <sup>3</sup>		
VME-8 h	: -	mg/m <sup>3</sup>	-	ppm
VLE-15 min.	: -	mg/m <sup>3</sup>	-	ppm
GWBB-8 h	: -	mg/m <sup>3</sup>	-	ppm
GWK-15 min.	: -	mg/m <sup>3</sup>	-	ppm
Momentary value	: -	mg/m <sup>3</sup>	-	ppm
EC	: -	mg/m <sup>3</sup>	-	ppm
EC-STEL	: -	mg/m <sup>3</sup>	-	ppm

## Profil Adapterfoam

### 8.2 Exposure controls:

#### 8.2.1 Occupational exposure controls:

- Use only in well ventilated area

#### 8.2.2 Environmental exposure controls: see heading 13

### 8.3 Personal protection:

#### 8.3.1 respiratory protection:

- In case of insufficient ventilation: gas mask with filter type A

#### 8.3.2 hand protection:

- Gloves

#### 8.3.3 eye protection:

- Protective goggles

#### 8.3.4 skin protection:

- Protective clothing

## 9. Physical and chemical properties

### 9.1 General information:

Appearance (at 20°C)	: Aerosol
Odour	: Characteristic
Colour	: Variable in colour

### 9.2 Important health, safety and environmental information:

pH value	: N.D.	
Boiling point/boiling range	: N.D.	°C
Flashpoint	: Contains extremely flammable components	
Explosion limits	: N.D.	vol%
Vapour pressure (at 20°C)	: N.D.	hPa
Vapour pressure (at 50°C)	: N.D.	hPa
Relative density (at 20°C)	: N.D.	
Water solubility	: Insoluble	
Soluble in	: N.D.	
Relative vapour density	: N.D.	
Viscosity	: N.D.	Pa.s
Partition coefficient n-octanol/water	: N.D.	
Evaporation rate		
ratio to butyl acetate	: N.D.	
ratio to ether	: N.D.	

### 9.3 Other information:

Melting point/melting range	: N.D.	°C
Auto-ignition point	: N.D.	°C
Saturation concentration	: N.D.	g/m <sup>3</sup>

# Profil Adapterfoam

## 10. Stability and reactivity

### 10.1 Conditions to avoid/reactivity:

- Unstable on exposure to heat

### 10.2 Materials to avoid:

- Heat sources, ignition sources, acids, bases

### 10.3 Hazardous decomposition products:

- May polymerize on exposure to temperature rise
- On heating: release of toxic/combustible gases/vapours: hydrogen cyanide
- On burning: release of toxic and corrosive gases/vapours: nitrous vapours, hydrogen chloride, carbon monoxide and carbon dioxide
- May polymerize with many compounds e.g.: (strong) bases and amines
- Reacts violently with (some) acids/bases

## 11. Toxicological information

### 11.1 Acute toxicity:

POLYMETHYLENEPOLYPHENYLISOCYANATE:

LD50 oral rat	: > 10000	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: > 5000	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

alpha, alpha', alpha''-1,2,3-PROPANETRIYL-tris(omega-HYDROXY-) POLY[OXY(METHYL-1,2-ETHANEDIYL)]:

LD50 oral rat	: 1500/2000	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: > 2000	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

ISOBUTANE:

LD50 oral rat	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: 658	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

PROPANE:

LD50 oral rat	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: 513	mg/l/4 h
LC50 inhalation rat	: 280000	ppm/4 h

## 11.2 Chronic toxicity:

POLYMETHYLENENPOLYPHENYLISOCYANATE:

EC carc. cat. : not listed  
EC muta. cat. : not listed  
EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed  
Carcinogenicity (MAC) : not listed  
Carcinogenicity (VME) : not listed  
Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : 3B  
Mutagenicity (MAK) : not listed  
Teratogenicity (MAK) : -

IARC classification : 3

DIMETHYL ETHER:

EC carc. cat. : not listed  
EC muta. cat. : not listed  
EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed  
Carcinogenicity (MAC) : not listed  
Carcinogenicity (VME) : not listed  
Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : not listed  
Mutagenicity (MAK) : not listed  
Teratogenicity (MAK) : D

IARC classification : not listed

11.3 Routes of exposure: inhalation, eyes and skin

## 11.4 Acute effects/symptoms (upon overexposure) :

**AFTER INHALATION:**

- Dry/sore throat
- Coughing
- Irritation of the respiratory tract
- Irritation of the nasal mucous membranes
- Runny nose

**FOLLOWING SYMPTOMS MAY APPEAR LATER:**

- Inflammation of the respiratory tract
- Risk of lung oedema
- Respiratory difficulties

**AFTER SKIN CONTACT:**

- Tingling/irritation of the skin

**AFTER EYE CONTACT:**

- Irritation of the eye tissue
- Lacrimation

## 11.5 Chronic effects:

- May cause sensitization by skin contact
- May cause sensitization by inhalation
- Contains substance with uncertain carcinogenic properties (polymethylenepolyphenylisocyanate)

**ON CONTINUOUS EXPOSURE/CONTACT:**

- Body temperature rise
- Tremor
- Feeling of weakness
- Headache
- Skin rash/inflammation
- May stain the skin
- Dry skin
- Risk of pneumonia

# Profil Adapterfoam

## 12. Ecological information

### 12.1 Ecotoxicity:

- No data available

### 12.2 Mobility:

- Volatile organic compounds (VOC): 17 %
- For other physicochemical properties see section 9

### 12.3 Persistence and degradability:

- biodegradation BOD<sub>5</sub> : N.D. % ThOD
- water : No data available
- soil : T ½: N.D. days

### 12.4 Bioaccumulative potential:

- log P<sub>ow</sub> : N.D.
- BCF : N.D.

### 12.5 Other adverse effects:

- WGK : 1 (classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : No data available
- Effect on waste water purification : No data available

## 13. Disposal considerations

### 13.1 Provisions relating to waste:

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 05 01 (waste isocyanates)
- Waste material code (Flanders): 015; 651
- Hazardous waste (91/689/EEC)

### 13.2 Disposal methods:

- Specific treatment

### 13.3 Packaging:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10 (packaging containing residues of or contaminated by dangerous substances)

## 14. Transport information



<b>14.1 Classification of the substance in compliance with UN Recommendations</b>	
UN-number	: 1950
CLASS	: 2.2
SUB RISKS	: -
PACKING	: -
PROPER SHIPPING NAME	: UN 1950, Aerosols
<b>14.2 ADR (transport by road)</b>	
CLASS	: 2
CLASSIFICATION CODE	: 5 A
DANGER LABEL TANKS	: -
DANGER LABEL PACKAGES	: 2.2
<b>14.3 RID (transport by rail)</b>	
CLASS	: 2
CLASSIFICATION CODE	: 5 A
DANGER LABEL TANKS	: -
DANGER LABEL PACKAGES	: 2.2
<b>14.4 ADNR (transport by inland waterways)</b>	
CLASS	: 2
CLASSIFICATION CODE	: 5 A
DANGER LABEL TANKS	: -
DANGER LABEL PACKAGES	: 2.2
<b>14.5 IMDG (maritime transport)</b>	
CLASS	: 2.2
SUB RISKS	: -
PACKING	: -
MFAG	: -
EMS	: F-D, S-U
MARINE POLLUTANT	: -
<b>14.6 ICAO (air transport)</b>	
CLASS	: 2.1
SUB RISKS	: -
PACKING	: -
PACKING INSTRUCTIONS PASSENGER AIRCRAFT	: 203/Y203
PACKING INSTRUCTIONS CARGO AIRCRAFT	: 203
<b>14.7 Special precautions in connection with transport</b>	
	: none
<b>14.8 Limited quantities (LQ)</b>	
	:

When substances and their packaging meet the conditions established by ADR/RID/ADNR in chapter 3.4, **only** the following prescriptions shall be complied with:  
 each package shall display a diamond-shaped figure with the following inscription:  
 - 'UN 1950'  
 or, in the case of different goods with different identification numbers within a single package:  
 - the letters 'LQ'

## 15. Regulatory information

Labelling in accordance with EC directives 67/548/EEC and 1999/45/EC (\*\*: see heading 16)



Extremely flammable



Harmful

Contains : polymethylenepolyphenylisocyanate

R20 : Harmful by inhalation  
R36/37/38 : Irritating to eyes, respiratory system and skin  
R42/43 : May cause sensitization by inhalation and skin contact

S23 : Do not breathe spray  
S36/37/39 : Wear suitable protective clothing gloves, and eye/face protection  
S38 : In case of insufficient ventilation, wear respiratory equipment  
S45 : In case of accident or if you feel unwell, seek medical advice (show the label where possible)  
S51 : Use only in well ventilated area

Keep away from sources of ignition - No smoking.  
Keep out of the reach of children.  
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.  
Do not pierce or burn after use.  
Do not spray on a naked flame or any incandescent material

Contains isocyanates. See information supplied by the manufacturer.

# Profil Adapterfoam

## 16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**N.A.** = NOT APPLICABLE  
**N.D.** = NOT DETERMINED  
**\*** = INTERNAL CLASSIFICATION

### (\*\*) Labelling:

The labelling of the substance described in this MSDS complies with the provisions of Directive 1999/45/EC of 31 May 1999, published in the Official Journal of the European Communities L 200 of 30/07/1999. This Directive replaces Directive 88/379/EEC of 7 June 1988, published in the Official Journal of the European Communities L 187 of 16/07/1988.

Member States shall apply the laws, regulations and administrative provisions referred to in article 22 of this Directive:

- (a) to preparations not within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2002; and  
(b) to preparations within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2004.

### Full text of any R-phrases referred to under heading 2:

R12 : Extremely flammable  
R20 : Harmful by inhalation  
R22 : Harmful if swallowed  
R36/37/38 : Irritating to eyes, respiratory system and skin  
R42/43 : May cause sensitization by inhalation and skin contact

### Exposure limits:

**TLV** : Threshold Limit Value - ACGIH US 2000  
**OES** : Occupational Exposure Standards - United Kingdom 1999  
**MEL** : Maximum Exposure Limits - United Kingdom 1999  
**MAK** : Maximale Arbeitsplatzkonzentrationen - Germany 2001  
**TRK** : Technische Richtkonzentrationen - Germany 2001  
**MAC** : Maximale aanvaarde concentratie - the Netherlands 2002  
**VME** : Valeurs limites de Moyenne d'Exposition - France 1999  
**VLE** : Valeurs limites d'Exposition à court terme - France 1999  
**GWBB** : Grenswaarde beroepsmatige blootstelling - Belgium 1998  
**GWK** : Grenswaarde kortstondige blootstelling - Belgium 1998  
**EC** : Indicative occupational exposure limit values - directive 2000/39/EC

**I** : Inhalable fraction = **T** : Total dust = **E** : Einatembare Aerosolanteil  
**R** : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust  
**C** : Ceiling limit

<b>a:</b>	aerosol	<b>r:</b>	rook/Rauch	(fume)
<b>d:</b>	damp (vapour)	<b>st:</b>	stof/Staub	(dust)
<b>du:</b>	dust	<b>ve:</b>	vezel	(fibre)
<b>fa:</b>	Faser (fibre)	<b>va:</b>	vapour	
<b>fi:</b>	fibre	<b>om:</b>	oil mist	
<b>fu:</b>	fume	<b>on:</b>	olienevel/Ölnebel	(oil mist)
<b>p:</b>	poussière (dust)	<b>part:</b>	particles	

### Chronic toxicity:

**K** : List of the carcinogenic substances and processes - the Netherlands 2002